

#Technical data

| Model                            |       |         | M4062  |                           | M4072       |  |
|----------------------------------|-------|---------|--|---------------------------|-------------|--|
|                                  |       |         | ROPS   | Cab                       | ROPS        | Cab  |
| Engine                           |       |         | Kubota   |                           |             |  |
| Engine type                      |       |         | V3307-CRS-TE4  |                           |             |  |
| Displacement/No of cylinders     |       | cm³     | 3,331 / 4  |                           |             |  |
| Rated speed                      |       | rpm     | 2,400  |                           |             |  |
| Rated power (97/68/EC)           |       | hp (kW) | 66 (48.8)  |                           | 74 (54.6)   |  |
| Fuel tank capacity               |       | l       | 70   | 90                        | 70          | 90   |
| Transmission                     |       |         | Kubota   |                           |             |  |
| Type – Main gear shift           |       |         | 6 speed synchronised; Option: Dual Speed   |                           |             |  |
| Range gear shift                 |       |         | 3 groups: transport/field/creeper  |                           |             |  |
| No of speeds                     |       |         | F18 / R18  |                           | New         | F18 / R18 (serial)<br>F36 / R36 with Dual Speed (optional) |
| Max travelling speed             |       | km/h    | 40 mit Eco-Drive   |                           |             |  |
| Shuttle shift                    |       |         | New  | electro-hydraulic shuttle |             |  |
| Main clutch                      |       |         | multiple wet disc  |                           |             |  |
| Brake type                       |       |         | Hydraulically operated wet disc brakes, with automatic front axle engagement (4WD) |                           |             |  |
| 4WD engagement                   |       |         | electro-hydraulic  |                           |             |  |
| Rear differential lock           |       |         | mechanical type  |                           |             |  |
| PTO                              |       |         |  |                           |             |  |
| Speed                            |       | rpm     | 540/540 Eco; Option 540/1,000  |                           |             |  |
| Activation                       |       |         | electro-hydraulic  |                           |             |  |
| Hydraulic                        |       |         |  |                           |             |  |
| Pump capacity                    |       | l/min   | 63   |                           |             |  |
| 3-point hitch                    |       |         | Quick-hitch lower link ends (Cat II)   |                           |             |  |
| Control system                   |       |         | Position and draft control   |                           |             |  |
| Lift capacity                    |       | kg      | 2,500  |                           |             |  |
| No. of hydraulic valves and type |       |         | Standard: 2; optional: 3   |                           |             |  |
| Standard tire size               |       | F/R     | F: 320/85R20; R: 420/85R30   |                           |             |  |
| Dimensions and weight            |       |         |  |                           |             |  |
| Length                           |       | mm      | 3,700  |                           |             |  |
| Height                           |       | mm      | 2,090*   | 2,580                     | 2,090*      | 2,580  |
| Width min–max                    |       | mm      | 1,850–2,150  | 1,950–2,165               | 1,850–2,150 | 1,950–2,165  |
| Wheelbase                        |       | mm      | 2,135  |                           |             |  |
| Tread width                      | front | mm      | 1,450–1,535  | 1,365–1,415               | 1,450–1,535 | 1,365–1,415  |
|                                  | rear  | mm      | 1,430–1,730  | 1,530–1,745               | 1,430–1,730 | 1,530–1,745  |
| Weight                           |       | kg      | 2,570  | 3,040                     | 2,570       | 3,040  |

\*with folded roller bar

Kubota (U.K.) Limited

Dormer Road Thame, Oxfordshire, OX9 3UN

Website: <http://www.kubota.co.uk>

Every effort has been made to ensure that the contents of this publication were accurate and up-to-date at the time of going to press. All rights reserved. No part of this publication may be reproduced in any form by any means, without prior permission of Kubota. Kubota reserve the right as a manufacturer to amend and update any specification or performance information without notice, if required.



For Earth, For Life  
Kubota

M

KUBOTA

M4002 SERIES

4062 – 4072

